

500TA HON-BIOEM

- Check the correct positioning wordFeatures
- Elegant & modern design
- 2.8 inches TFT display
- GUI interface for easy operation.
- USB support
- Built-in latest fingerprint algorithm
- Built-in SSR excel software
- Short key s to select the In and Out status
- Inbuilt backup battery
- Simple access control or external bell




Introduction

HON-BIOEM-500TA is a fingerprint time & attendance terminal With SSR report(self-service Report) stored in the time clock. The 2.8inch TFT screen can display more information vividly, including fingerprint image and verification result .

TCP/IP communication is a standard function which makes sure the data transmission between terminal and PC can be easily done within few seconds. Internal backup battery insures the device work normally when the power cuts off suddenly.

CONFIGURATION



DIMENSION (MM)



Specifications	
Display	2.8 inch TFT Screen
Fingerprint capacity	500
Id card capacity	500
Log capacity	50,000
Communication	TCP/IP
Interface	USB Supported
Standard functions	Schedule bell ,Workcode, DLST, SSR report, Self-Service Query, Automatic Status Switch , T9input, 9 digit UserID, ID card, backup battery, external bell.
Supported software	EASYTIME3.0
Card supported	EM card
Access control function	Door Lock & Exit button
Power supply	DC 5V 0.8A
Operating temp	00C-450C
Operating humidity	20%-80%
Dimension	185X140X30mm

ORDERING INFORMATION

Part code	Description
HON-BIOEM-500TA	Honeywell Bio Terminal with EM-500 User

For more information,

<https://honeywellbuildings.in>

Call: 1-800-103-0339

Email: HBT-Indiabuildings@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43,
Block C, Sushant Lok Phase - I,
Gurgaon - 122 002